Proxima DP6850 Projector
Technical and Functional Specifications

Native Resolution	• XGA (1024 x 768)
Resolution Supported	• XGA (1024 x 768), Fit-to-View display of VGA (640 x 480),SVGA (800 x 600), SXGA (1280 x 1024),Mac (640 x 480, 1280 x 1024)
Brightness	• 1500 ANSI lumens
Contrast Ratio	• 100:1 ANSI
Computer Compatibility	• IBM PC or compatibles, Apple Macintosh
Video Compatibility	• PAL B, G, H, I, M, N; NTSC 3.58 / 4.43; SECAM
Display Technology	• 1.3" polysilicon LCD x 3
Number of Colors	• 16.7 million
Input Sources	• 2 computer, 2 audio, 1 video, 1 S-video, 1 USB mouse
Output	• Computer RGB (HD-15), Stereo audio (mini-jack)
H-Sync Range	• 15 - 100 kHz
V-Sync Range	• 43.5 - 130 Hz
Bandwidth	• 135 MHz
Horizontal Resolution (TV Lines)	• 500 TV Lines
Keystone Correction	• 20°, 20:1 upward, digital keystone correction
Projection Lens	• Motorized zoom and focus. f = 49 - 64 mm, F/1.7 - 2.3, 1.3:1 zoom ratio
Projection Distance	• 3.6 to 35 ft (1.1 to 10.7 m)
Aspect Ratio	• std:4:3 - wide:16:9
Image Size	• 2.0 ft to 24.3 ft (.6 m to 7.41 m)
Throw Ratio	• 1.8:1 to 2.4:1 (image width: throw dist.)
Projection Method	• front/rear, desktop/ceiling
Audio	• 2 x 1-watt stereo
Remote Control	• Full functionality remote with mouse control and laser pointer
Lamp (Life)	• 190 watt UHB (1,500 hours to 50% brightness)
Dimensions	• 11.5" W x 15.5" L x 4.7" H (29.1 cm W x 39.5 cm L x 11.9 cm H)
Weight	• 13.2 lbs. (6.0 kg)
Power Consumption	• 320 watts
Power Requirements	• 90 to 132V / 198 to 264V (+/- 10%) at 50/60 Hz
Operating Temperature	• 41°F to 95°F (O°C to 35°C)
On-Screen Menu Languages	• English, French, Spanish, Italian, German, Norwegian, Dutch
Audible Noise	• 40 db
Approvals	• CE, UL, cUL, TUV, FCC Class A
Security	• Kensington ® lock compatible
Warranty	• Two years on parts and labor (excluding lamp)

Copyright © 1997-2004 InFocus Corporation.
All Rights Reserved.